

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4612)

-----  
Set 1/4 sec. post, from which  
    A Fir 30" dia., bears N.10°W., 40 lks. dist.  
    A Fir 10" dia., bears N.85°E., 13 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - Wit: C. Crocker; Blumburg; Will Long; Carpenter - Dec. 1, 1922 - Vol. 3 Pg. 131; M 2-8

-----  
Reset midway between section corners to North and South.  
Drove Yew wood stake and marked the following trees:  
    Fir 14" dia., bears N.46°E., 17.4 ft.  
    Fir 14" dia., bears S.27°E., 40 ft. at 25° slope.  
Corner on steep rocky hill side.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-7

-----  
Found - Orig. 30" now 48" Fir N.10°W., 26.4 ft. Previously opened & "BT" scribe on face. Open higher & find axe notch just above "BT". Also very faint "1/4S" bark scribe.  
    Orig. 10" now 24" Fir N.85°E., 8.6 ft., previously opened, no scribing found.  
    No trace of Stewart's BTs as recorded in 1922.  
Set Brass cap at cor. mkd: County Surveyor's Office, 1966  
    T26S 1/4 S 16|S 15 R7W.  
New BTs - 8" Laurel N.17°W., 63.4 ft. mkd. 1/4 S16 CS BT.  
    31" D.Fir N.58°E., 49.2 ft. mkd. 1/4 S15 CS BT.  
This corner lies on very steep East slope.

Ronald L. Rice, Ward NW - Dec. 2009 - M 160-20

-----  
Found - 3" DCSO BC dated 1966 with the following accessories  
    29" D.Fir bears N.85°E., 8.6' - healed face.  
    21" Madrone bears N.17°W., 63.4' - healed face.  
    42x30" D.Fir staub bears N.10°W., 26.4' - opened face.  
    31x8" D.Fir staub bears N.58°E., 49.2' - scribing visible.