

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4612)

-----  
Set post cor. of secs. 9, 10, 15 and 16, from which  
A Fir 10" dia., bears N.78°E., 15 lks. dist.  
A Fir 10" dia., bears S.41°E., 18 lks. dist.  
A Fir 10" dia., bears S.71°W., 17 lks. dist.  
A Fir 8" dia., bears N.25°W., 190 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - Wit: C. Crocker; Blumburg; Will Long; Carpenter - Dec. 1, 1922 - Vol. 3 Pg. 131; M 2-8

-----  
Reset from one original BT and two stumps. I drove an Iron pipe and marked the following trees:  
Fir 18" dia., bears S.88°W., 24.0 ft.  
Fir 30" dia., bears S.20°E., 27.9 ft.  
Fir 30" dia., bears N.71°E., 9.8 ft.  
Fir 20" dia., bears North 21.7 ft.

Doug. County Surveyors Office - Milo Godfrey; Vernon Tracy; Mike Stone - Dec. 1962/Jan. 1963 - C.S. File 49/129-11

-----  
Found - 3/4" I.Pipe set by Stewart in 1922.  
34" Fir stump N.71°E., 9.8 ft., shows good scar.  
28" Fir stump North, 21.7 ft. bark scribing visible "BT".  
42" Fir S.20°E., 27.9ft. (to face) bark scribing visible, tree alive & in good condition.  
26" Fir S.88°W., 24.0 ft. (to center) bark scribing visible. Blaze & rescribe this tree "T26S R7W S16 CS BT".  
DID NOT SET BRASS CAP.  
New BTs - 24" D.Fir N.60°E., 47.0 ft. mkd: T26S R7W S10 CS BT.  
6" W.Fir N.45°W., 7.1 ft. mkd: S9 CS BT.  
Corner lies on rocky bench at foot of steep North slope.

Bureau of Land Management remonumentation of corner. By Donald Beck under Group #350, April 30, 1963 (DCSO records Volume 33 Page 13664)

-----  
The cor. of secs. was perpetuated and recorded by Stewart in 1922, and again in 1963, by Deputy Co. Surveyor, Milo Godfrey, monumented with an iron pipe, 1" dia., firmly set, projecting 3" above the ground, from which the only remaining bearing tree:  
A sawed Fir stump 33" dia., bears N.78°E., 15 lks. with a healed blaze. continued next page



TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

53" D.Fir bears S.18½°E., 29.0' bark scribe visible.  
39" D.Fir bears N.59°E., 46.9' - healed face.  
37" D.Fir bears S.89°W., 24.4' - healed face.  
20" W.Fir bears N.48°W., 7.6' - healed face.

David Edwards - For: CH Sheldon LP - 1/2022 - M180-39  
-----  
Found - BLM Brass cap  
15" diam. laurel N.71°E., 35.0' no marks.  
29" diam. cedar stump S.57½°E., 23.5'  
13" diam. fir S.34°W., 13.5' no marks  
The B.Oak S.77½°W., is down.  
21" diam. B.Oak W/H.B. N.68°W., 21.0'  
Set 6 foot steel post 2' North.

Fd. as per record 11/2023 by D. Edwards 2023-0037