

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12 1855 (DCSO records, Volume 11 Page 4614)

Set 1/4 sec. post, from which
 A Fir 24" dia., bears S.88°E., 31 lks. dist.
 A B.Oak 10" dia., bears S.86°W., 28 lks. dist.

William S. Barnes, For: Thomas - April 1970, M 39-63

Set - Brass cap.
BTs - 12" W.Fir N.85°W., 37.4 ft. mkd. "1/4 S4 T26S R7W BT
 27" W.Fir S.87°E., 41.0 ft. mkd. "1/4 S3 T26S R7W BT

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/1/2000 - C.S. File 66/16-31

Found - Brass cap/iron pipe, properly marked, protrudes 7"
 above ground.
 Fence lines extend North, West, & East from corner.
 1970 NW BT now gone
 27" now 24" dia., 6 ft. high badly rotted W.Fir
 stump with scribing visible "T26S R7W 1/4 S3 BT"
 bears S.87°E., 41.0 ft. 1970
New - 10" dia., D.Fir double blazed & scribed "1/4 S3 CS BT"
 bears N.42 1/2°E., 3.5 ft.
 15" dia., Yew double blazed & scribed "1/4 S3 CS BT"
 bears S.44 1/2°E., 23.2 ft.
 5" dia., W.Fir double blazed & scribed "1/4 S4 CS BT"
 bears N.26 1/2°W., 10.8 ft. ft.