

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4609)

Set 1/4 sec. post, from which
 A B.Oak 16" dia., bears N.65°W., 54 lks. dist.
 A B.Oak 16" dia., bears S.45°W., 31 lks. dist.

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838, Survey May 1971-Aug. 1974 (DCSO records Volume 37 Page 15170)

Point for the 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
 T 26 S R 7 W
 1/4 S 27
 S 34
 1974

from which
 A Fir 11" dia., bears N.48 1/2°E., 69 lks. mkd. 1/4 S27 BT.
 A Fir 12" dia., bears S.57°E., 38 lks. mkd. 1/4 S34 BT.
The corner is located in woven wire fence, extending N & S.

Fd. BC by D. Bentz, 4/1991 - 1991-0054
Fd. BC by M. Brittain, 9/2013 - 2013-0031