

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4611)

Set 1/4 sec. post, from which
 A Fir 8" dia., bears S.40°E., 4 lks. dist.
 A Fir 6" dia., bears N.35°W., 8 lks. dist.

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records Volume 37 Pages 15172-73)

Point for the 1/4 cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T 26 S R 7 W

1/4 S 22
 S 27

1974

from which

 A Fir 6" dia., bears N.23 1/2°E., 115 lks. dist., mkd.
 1/4 S22 BT.

 A Fir 8" dia., bears S.11 1/2°E., 24 lks. dist., mkd.
 1/4 S27 BT.

 A corner of woven wire fences extending E. and S.,
 bears N.40°W., 0.10 chs. dist.

Fd. Ok - Jan. 1994 - by Harold Stockhoff - M 118 - 23