TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4612)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.65°W., 24 lks. dist.
A Fir 18" dia., bears S.25°W., 27 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - Wit: C. Crocker, Blumburg; Will Long, Carpenter - Dec. 1, 1922 - Vol. 3 Pg 131; M 2-8

Reset from one O.B.T. and one stump. Drove an Iron pipe and marked the following trees:
W.Fir 18" dia., bears S.4½°W., 23.7 ft.
W.Fir 10" dia., bears N.54°E., 27.5 ft.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-2

Found - 3/4" I.Pipe with elbow on top.
10" now 12" W.Fir N.54°E., 27.5 ft., rotted stump 6" high, no scribe.
18" now 26" W.Fir S.4½°W., 23.7 ft., now stump. Open and find scribe.
Set Brass cap at cor. mkd: County Surveyors S 15
T26S ¼ S 22 R7W
Office, 1966
New BTs - 10" W.Fir N.26°W., 8.4 ft. mkd. ¼ S15 CS BT.
21" D.Fir S.22°W., 37.5 ft. mkd. ¼ S22 CS BT.
E-W fence bears South 3.0 ft.

Fd. Ok - Jan 1994 - by Harold Stockhoff - M 118 -23 (No tag on W.Fir BT & D.Fir BT now stump)

Found ok by E. Monrean, Mar. 2004 - M146-2