

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4613)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Fir 12" dia., bears N.9°E., 60 lks. dist. A Fir 12" dia., bears S.75°W., 44 lks. dist.</p>
<p>G.G. Stewart, Deputy Co. Surveyor Wit: C. Crocker; Blumburg; Will Long; Carpenter - Dec. 1, 1922 - Vol. 3 Pg. 131; M 2-8</p> <p>-----</p> <p>Reset from one original bearing tree and one stump. Drove an I. Pipe and marked the following trees: Fir 30" dia., bears S.50°W., 28.0 ft. Fir 30" dia., bears N.9½°E., 28.6 ft.</p>
<p>Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-9</p> <p>-----</p> <p>Found - 1/2" I.P. and stump of BT, as recorded by Stewart. 30" now 48" Fir S.50°W., 28.0 ft., bark scribed, now stump. No trace original BTs or other BT. Set Brass cap in mound of stone 24" high mkd. T26S ¼ $\frac{S}{S} \frac{10}{15}$ R7W County Surveyors Office, 1966 New BTs - 7" W.Fir N.73°E., 86.6 ft. mkd. ¼ S10 CS BT. No trees close in Section 15. Corner lies 15.0 ft. E. of SW - NE fence on steep, rocky N. slope.</p>
<p>Fd. OK, H. Pieske, May, 1988, M 106-25</p>
<p>David Edwards - For: CH Sheldon LP - 1/2022 - M180-39</p> <p>-----</p> <p>Found - DCSO brass cap loose in rocks. Rebuilt mound of stones. SW - NE fence is 15' West 28" diam. fir N.81°E., 72.6' (Rec N.73°E., 86.6')</p> <p>New BT - An 18" diam. fir scribed "¼ S15 BT" bears S.81°E., 23.5' A six foot steel post is set 2' East.</p>
<p>Fd. as per record 11/2023 by D. Edwards 2023-0037</p>
<p> </p>