

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION (WC) 1/4 Cor. For Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original, Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4602)</p> <p>-----</p> <p>Set ¼ sec. post, from which A W.Oak 10" dia., bears S.79°W., 280 lks. dist. A W.Oak 12" dia., bears S.16°E., 260 lks. dist.</p>
<p>M.B. Germond, August 18, 1908 - Vol. 2 Page 146</p> <p>-----</p> <p>I set a Sandstone, 4" x 8" x 16" and note that BTs are as per Government field notes.</p>
<p>F.C. Frear; B.A. Lane; Carl Becker, May 18, 1935 (no record source found, see "old" corner book, Page 76)</p> <p>-----</p> <p>Reset this corner from one old BT, scribe marks plain. Set a 2" x 30" Iron pipe 20 ft. East on side of road for Witness Corner, from which A 10" W.Oak bears N.43½°E., 42.0 ft. A 12" W.Oak bears S.55½°E., 61.5 ft.</p>
<p>Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-25</p> <p>-----</p> <p>Found - 2" I.Pipe 6" below surface of ground. Orig. 12" now 26" W.Oak S.16°E., 171.6 ft. Open &amp; find very faint reverse scribed axe notch. No trace of BTs recorded by Frear nor other orig. BT.</p> <p>Actual corner falls in road. I.P. is 20 ft. East of corner. Set Brass cap alongside I.P. for Wit. Cor. mkd: Co. Surv. Office, 1966 T26S R7W Wit. Cor. ¼ S34 S35 20 ft. W. to Cor. New BTs- 13" W.Oak N.1°E., 134.8 ft. mkd: W.C. ¼ S35 CS BT 9" W.Oak S.28°E., 39.0 ft. mkd: W.C. ¼ S35 CS BT. No trees available to West of line.</p> <p>Witness Corner falls in N-S fence on East side of road, course N &amp; S &amp; 35.6 ft N of fence corner, fences N-S and NE.</p>
<p>Doug. County Surveyors Office - John M. Powell; W. Penley July 12, 1971 - C.S. File 54/23-18</p> <p>-----</p> <p>Found - 13" W.Oak now 14" N.1°E., 134.8 ft. scribe visible. 9" W.Oak now 11" S.28°E., 39.0 ft. scribe visible. Brass cap set for Wit. Cor. mkd. and I.P. alongside.</p> <p>As this cor. will now fall in new road R/W, I remove said cap and move it 30 ft. East. I also remark cap to read "Wit. Cor. 50 ft. W. to".</p> <p>Continued next page</p>

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION (WC) 1/4 Cor. For Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 16" D.Fir S.9°E., 57.0 ft. scribed W.C. ¼ S35 CS BT.  
10" W.Oak S.58°E., 72.5 ft. scribed W.C. ¼ S35 CSBT.

Fd. OK, V.R.T. July 1973 - C.S. File 56/34-16

Bureau of Land Management resurvey by Peterson, etal under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records Volume 37 Page 15166)

-----  
1/4 Corner determined at record bearing and distance from the remains of an original bearing tree:  
A W.Oak stump 26" dia., bears S.16°E., 260 lks. dist. with old axe marks visible on decayed blaze.  
At the corner point  
Drive an iron pin, 6" long, 5/8" dia., 6" in the ground level with road surface.  
Corner point is located in center of W. land of Elgarose Road paved, 40 lks. iwde, bears N. and S.  
From this point, a reference monument established by the DCSO in 1971, bears East, 0.75 chs. dist., monumented with an iron post, 1" dia., firmly set, projecting 6" above ground with properly mkd. cap.  
from which  
A Fir 16" dia., bears S.9°E., 87 lks. dist., with scribe marks WC ¼ S35 CS BT visible on open blaze.  
A W.Oak 9" dia., bears S.58°E., 110 lks. dist., with scribe marks WC ¼ S35 CS BT visible on open blaze.

Fd OK, Donald Bentz, November 1991, M 112-51  
Fd Ok, Mark Heimburger, Feb. 1994, 1994-0024 A & B