

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4603)

Set post, cor. secs. 26, 27, 34 and 35, from which
A W.Oak 10" dia., bears N.42°E., 141 lks. dist.
A Fir 20" dia., bears N.17°W., 94 lks. dist.
A Fir 24" dia., bears S.75°E., 40 lks. dist.
A Maple 14" dia., bears S.8°W., 80 lks. dist.

M.B. Germond, August 18, 1908 - Vol. 2 Page 146

Set for sec. corner, an Iron Pipe 1½" dia., driven 2 ft. in the ground. I note most of the Gov't BTs are still preserved.

Searched for, not fd, V. Tracy, March 1966 C.S. File 54/23-1a

Bureau of Land Management resurvey by Peterson, etal under Group #'s 744 and 838 - Survey May 1971-Aug. 1974 (DCSO records, Vol. 37 Page 15165)

Section corner determined at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

T 26 S R 7 W
S 27 | S 26
S 34 | S 35
1974

from which
An Alder 12" dia., bears N.64°E., 230 lks. mkd. T26S R7W
S26 BT.
A Fir 23" dia., bears S.22°E., 310 lks., mkd. T26S R7W
S35 BT.
A Fir 21" dia., bears S.27¾°W., 206 lks., mkd. T26S R7W
S34 BT.
A power pole, No. 149, bears N.47½°W., 41 lks.
The corner is located on the NW. cor. of Elgarose Road, paved, 40 lks. wide, bears E. and S.

Fd. BC by D. Bentz, 4/1991 - 1991-0054

Fd. BC by M. Brittain, 9/2013 - 2013-0031

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/29/2023 - C.S. File 67/55-65

Found - 1974 3¼" BLM brass cap (properly mkd), down 4"
26" Alder N.64°E., 154.5 ft. (rec. 230 lks) blaze
not visible. Continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40" D.Fir S.22°E., 203.0 ft. (rec. 310 lks) full
healed single blaze.
Power pole No. 149, N.47½°W., 26.0 ft. (rec. 41 lks)
Undermined by stream, likely to be replaced soon.
32" W.Fir, S.27¾°W., 136.0 ft. (Rec. 206 lks) fully
healed single blaze.
New - 5/8"x30" I.Rod with DCS0 plastic cap East 7.2 ft.
flush.
5/8"x30" I.Rod with DCS0 plastic cap East 47.0 ft.
flush.
Caps are set flush in road shoulder.
Note - Monument on West edge of Elgarose Rd. In fill slope.
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 160174.210 E 118144.819