

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4603-04)

Set 1/4 sec. post, from which
 A B.Oak 16" dia., bears S.65°E., 11 lks. dist.
 A B.Oak 8" dia., bears N.22°W., 19 lks. dist.

Bureau of Land Management resurvey by Peterson, etal under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records, Volume 37 Pages 15166-67)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an Iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd: T 26 S R 7 W

1/4
S 27 | S 26
1974

from which
 A Fir 10" dia., bears N.34°E., 78 1/2 lks. dist., mkd.
 1/4 S26 BT.
 An Oak 13" dia., bears N.35°W., 24 lks. dist. mkd.
 1/4 S27 BT.

Fd. OK, Don Bentz, August 1991 - Partition 1991-0056