

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4605)

Set post cor. secs. 14, 15, 22 and 23, from which
A Fir 8" dia., bears S.75°E., 46 lks. dist.
A Fir 36" dia., bears S.52°W., 42 lks. dist.
A Fir 30" dia., bears N.22°W., 54 lks. dist.
A Fir 6" dia., bears N.5°E., 41 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - Wit: C. Crocker; Blumburg; Will Long, Carpenter - Dec. 1, 1922 - Vol. 3 Page 131; M 2-8

Reset from old stump and one tree. No scribe marks visible. Drove Iron pipe and marked the following trees:
Fir 36" dia., bears S.63½°W., 46.1 ft.
Fir 30" dia., bears N.18°W., 27.0 ft.
Fir 30" dia., bears S.42½°E., 22.7 ft.
Fir 12" dia., bears East 31.9 ft.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-8

Found - 3/4" I.Pipe with elbow on top.
30" now 41" Fir N.18°W., 27.0 ft., stump, no scribe found.
36" now 48" Fir stump S.63½°W., 46.1 ft., bark scribe.
30" now 42" Fir stump S.42½°E., 22.7 ft. bark faced off, badly flaked, no scribe.
12" now 24" Fir East 41.9 ft. (Recorded as 31.9 ft.)
Open and find "BT" scribe.

Set Brass cap at cor. mkd: County Surveyors T26S S 15|S 14 R7W
Office, 1966 S 22|S 23
New BTs - 5" W.Fir N.64°E., 12.2 ft. mkd. S14 CS BT.
14" B.Oak N.31°W., 23.9 ft. mkd. T26S R7W S15 CS BT.
6" W.Fir S.20°W., 23.1 ft. mkd. S22 CS BT.
5" D.Fir S.23°E., 24.7 ft. mkd. S23 CS BT.
W-E fence bears 8.0 ft. South.

Fd. Ok Jan., 1994 by H. Stockhoff - M118-23
Found OK by E. Monrean, Mar. 2004 - M146-2
Fd BC 4/2018 R.Quimby 2018-0011A-B