

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 35 & 36 of T25-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 9 Page 3856)

-----  
Set post corner secs. 2, 3, 35 and 34, from which  
A B.Oak 24" dia., bears N.40°E., 708 lks.  
A B.Oak 30" dia., bears S.14°E., 738 lks.  
A B.Oak 24" dia., bears S.40°W., 1056 lks.  
A B.Oak 24" dia., bears N.89°W., 1197 lks.

Bureau of Land Management resurvey by G. Steven Popken under Group # 869. Survey May-July 1975 (DCSO records, Volume 37 Page 15302) (Duplicate information was submitted prior to survey approval & is filed in C.S. File 57/33)

-----  
Corner determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N.40°E., 708 lks.  
A B.Oak 59" dia., bears N.89°W., 1,197 lks. with scribe marks BT visible on opened blaze.

At the corner point

Set an Iron post 28" long, 2½" dia., 34" in the ground, with top 6" below surface, with brass cap mkd:

T 25 S R 7 W  
S 34 | S 35  
S 3 | S 2  
T 26 S  
1975

from which new bearing trees

A Fir 20" dia., bears N.65½°E., 553 lks., mkd. T25S R7W S35 BT.

A Fir 12" dia., bears S.80°W., 1,011 lks., mkd. T26S R7W S3 BT.

No other suitable trees available within limits  
Corner is located in open cultivated field.

FD. BC by D. Edwards, 7/2006 - M151-13