

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4606)

Set 1/4 sec. post, from which
 A B.Oak 6" dia., bears S.70°E., 36 lks. dist.
 A B.Oak 12" dia., bears N.61°W., 181 lks.

G.G. Stewart, Deputy - Wit: C.Crocker; Blumburg, Will Long; Carpenter - Dec. 1, 1922 - Vol. 3 Pg. 131; M 2-8

Reset from one original BT, rotted. Drove an Iron pipe and marked the following trees:
 Fir 14" dia., bears S.43°W., 99.1 ft. (OBT)
 B.Oak 18" dia., bears N.61°W., 119.5 ft.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-10

Found - 1/2" I.P. and BTs as recorded by Stewart.
 Orig. 12" now 28" B.Oak N.61°W., 119.5 ft.
 previously opened & rebark scribed in
 1922, "CS 1/4"
 No trace of other orig. BT.
 14" now 26" D.Fir S.43°W., 99.1 ft., shows good
 scar. (We do not open)
Set brass cap at cor. mkd. County Surveyor's Office, 1966 T26S 1/4 S 11 S 14 R7W
Deposit old corner pipe alongside.
New BTs - 8" D.Fir N.85°E., 19.7 ft. mkd. 1/4 S11 CS BT.
 12" D.Fir S.42°W., 7.0 ft. mkd. 1/4 S14 CS BT.
Corner lies at fence corner on steep N. slope, fences N-W-E.