

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 2; & Sec. 35 of T25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 9 Page 3855)

Set ¼ Sec. post, from which
 A B.Oak 18" dia., bears S.89¾°W., 806 lks.
 A B.Oak 12" dia., bears N.89¾°W., 792 lks.

Steve Wetherell, BLM, June 9, 1975 - C.S. File 57/33

(Unofficial, survey pending)
Found - B.Oak snag, 37", N.89¾°W., 792 lks., scribe mark
 T visible.
 B.Oak snag, 38", S.89¾°W., 806 lks., scribe marks
 4 S BT.
Set 2½" Iron pipe 18" in ground, in mound of stone 4 ft. base
to top, with brass cap mkd. T25S R7W
 1/4 $\frac{S\ 35}{S\ 2}$
 T26S
 1975
Sand stone boulder 4' x 4' in place N.35°W., 85½ lks. "X BO".

Doug. County Surveyors Office - R.B. Kimberling, Deputy -
P. Earle - May 19, 1977 - C.S. File 59/34-19

Found - Orig. 18" B.Oak, now 40" measured below fork, half
 dead, bears S.89¾°W., 532.0 ft. Found opened
 blaze and scribing "BT".
 Orig. 12" B.Oak now 37" dead trunk (tree is triple
 trunked at ground) bears N.89¾°W., 522.7 ft.
 Found opened blaze & scribing "B" in cut out
 section.
 A 4 ft. mound of stone at corner location.
 A 4 ft. x 4 ft. outcropping in sandstone ledge mkd.
 "X BO" bears N.35°W., 56.2 ft.
Set A 1" I.P. 36" long, set 33" in ground in mound of stone 4
ft. base to a cap mkd: T25S R7W 1/4 S35 S2 T26S 1977.
Set a metal fence post 2.0 ft. North of B.C w/ sign attached.
New Bearing Object:
 A 2' x 3' outcropping in sandstone ledge mkd. "BO"
 on horizontal surface with 3" "X" on surface
 facing corner bears S.13½°E., 63.7 ft.
Set a metal fence post 18" West of "X" with witness post sign
attached.