

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, Under Group #57, dated April 12, 1855 (DCSO records, Vol. 11 Page 4596)

Set post, cor. secs. 25, 26, 35 and 36, from which
A B.Oak 12" dia., bears S.62°W., 47 lks. dist.
A B.Oak 24" dia., bears N.65°W., 21 lks. dist.
A B.Oak 30" dia., bears N.84°W., 40 lks. dist.
A B.Oak 12" dia., bears S.83°E., 62 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; S.A. Bilow; Clete Putnam - June 26, 1959
C.S. File 49/129-8

Found - Brass cap at cor. mkd: County Surveyor's Office
T26S R7W $\frac{26}{35} \frac{25}{36}$

(I found no record source for this brass cap. Possibly set by Richardson and Godfrey in 1949) VL, 9/92

Orig. 12" now 20" Oak snag, S.83°E., 40.9 ft., shows good scribing "S36".

No trace of other original BTs found.

I find BTs. thus, probably scribed at time cap was set:

Now 14" R.Fir bears N.72°E., 4.6 ft. shows some scribing.

Now 10" Laurel bears S.23°E., 12.9 ft. shows good scribing "S36 CS".

Now 11" R.Fir bears S.49°W., 33.0 ft. shows good scar.

I do not find NW BT.

I scribe 12" R.Fir N.73°W., 39.0 ft. "S26 T26S R7W CS BT".

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO record, Vol. 37 Page 15165)

Found corner perpetuated by person(s) unknown, further perpetuated and recorded by the Douglas Co. Surveyor in 1959, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap mkd: T 26 S

$\frac{26}{35} \frac{25}{36}$
7 W

from which the remains of an original bearing tree
(Cont. Next Page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole, bears S.83°E., 62 lks. dist., with a down oak snag alongside, 20" dia., with scribe marks S36 visible on open blaze.
and bearing trees of which I have no record
A fir 17" dia., bears N.72°E., 7 lks. dist., with healed blaze.
A Madrone 10" dia., bears S.23°E., 19½ lks. dist., with healed blaze.
A fir 16" dia., bears S.49°W., 49 lks. dist., with healed blaze.
and a bearing tree mkd. in 1959
A fir 15" dia., bears N.75°W., 59 lks. dist., with healed blaze.
Add marks BLM 1974 to brass cap.

Fd. OK, Oct. 1981, K. DeGroot, M 89-51
Fd. OK, D. Bentz, Dec. 1991, Partition 1992-0012