

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4598)

Set 1/4 sec. post, from which
 A W.Oak 9" dia., bears S.80°E., 48 lks. dist.
 A W.Oak 10" dia., bears N.55°W., 30 lks. dist.

Doug. County Surveyors Office - V. Tracy; V. Perron - Oct. 9, 1970 - C.S. File 54/23-15

Found - Orig. 10" now 26" W.Oak, down, N.55°W., 19.8 ft., find "BT" scribe in sawed stump.
 No trace other orig. BT.
Set brass cap at cor. mkd: County Surveyor's T26S R7W Office, 1970 1/4 S 23|S 24
Set brass cap in E-W fence line, 1.0 ft. west of fence corner, fences E-W and N. On N. side of graveled road.
New BTs - 10" W.Oak S.1°E., 54.2 ft. mkd: "1/4 S24 CS BT".
 9" W.Oak N.46°W., 62.5 ft. mkd. "1/4 S23 CS BT".
Set 5/8" Iron rod in fence line N.88°E., 20.05 ft.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - May 2, 1996 - C.S. 64/69-3

Found - 2 1/2" Brass cap on a 1 1/2" O.D. iron pipe protruding 8" above ground.
 24" Dia. 2' high rotted oak stump no evidence of blazes or scribing visible, bears N.55°W., 19.8'.
 9" W.Oak now 20" dia. B.Oak with a fully healed blaze, bears N.44°W., 62.5'.
 25" Dia. W.Oak with a fully healed double blaze, bears S.1°W., 54.2'. (rec. S.1°E., 54.2')
Note: 5/8" I.R. (rec. N.88°E., 20.5' per 1970 DCSO renewal) not looked for.
New BTs - 15" B.Oak, double blazed and scribed "1/4 S23 CS BT", bears N.10°W., 51.8'.
 13" grand fir, double blazed and scribed "1/4 S23 CS BT", bears N.79 1/2°W., 96.8'.

Fd. Ok by Jody Frasier, 5/2006 - M152-10