TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4599)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.84°E., 53 lks. dist.
A B.Oak 12" dia., bears N.47°W., 31 lks. dist.

Douglas Co. Surveyors Office - G.G. Stewart, Dep. - Witness: C. Crocker, Blumburg, Will Long, Carpenter - Dec. 1, 1922

Reset from two orig. BTs, both badly rotted.
Set - Iron pipe and marked:
B.Oak 18" dia., bears N.61°W., 45 ft.
W.Oak 18" dia., bears N.18°E., 39.2 ft.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March 1966 - C.S. File 54/23-3

Found - ½" I.Pipe in E-W fence.
18" now 24" B.Oak N.18°E., 39.2 ft., almost dead, shows good scar. Open & find fragmentary reverse "¼", face rotted away.
No trace of orig. BTs, nor other BT.
Set brass cap at cor. mkd: County Surveyor's Office, 1966
T26S R7W ¼ S14|S13
Set BC/IP alongside I.P. and build mound of stone around cor.
New BTs - 17" B.Oak S.63°E., 24.6 ft. mkd. ¼ S13 CS BT.
7" B.Oak N.25°W., 12.2 ft. mkd. ¼ S14 CS BT.
This cor. lies 50 ft. E. of top of ridge, course S.45°E. & N.45°W.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - July 17, 1996 - C.S. 64/69-13

Found - 2½" Brass cap on a 1½" O.D. Iron pipe protrudes 10" above a 3' dia. mound of stone.
No evidence of orig. BT's Fd.
No evidence of NW BT from 1922
27" dia. W.Oak, with a previously opened unhealed blaze, no scribing visible, bears N.18°E., 39.2'.
19" dia. W.Oak, with a fully healed double blaze, bears S.63°E., 24.6'.
9" dia. W.Oak, with a fully healed double blaze, bears N.25°W., 12.2'.
New BTs- 7" W.Oak, double blazed and scribed "¼ S14 CS BT", bears N.74°W., 19.7'
Corner lies in an east-west fence line approx 50' east of ridge top.

Fd. Brass cap by N. Hibbs, 1/2007 - 2007-0031