

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, Under Contract #57 dated April 12, 1855 - (DCSO records, Volume 11 Pages 4599-4600)

Set post, cor. secs. 11, 12, 13 and 14, from which
A B.Oak 30" dia., bears N.50°E., 63 lks. dist.
A B.Oak 18" dia., bears N.70°W., 26 lks. dist.
A B.Oak 18" dia., bears S.20°W., 25 lks. dist.
A B.Oak 16" dia., bears S.20°E., 71 lks. dist.

F.C. Frear - Wit. C.C. Long; P.D. Wolford, July 15, 1920
(No source record found, see "old" Cor. book, Page 76)

Reestablished from old BTs which I remarked, and set 1" x 30" Iron pipe for corner.

Doug. County Surveyors Office - Ben B. Irving, Surveyor
A.R. Evans, R.L. Matthews - March 28, 1950 - M 9-38

Sec. cor. identified from O.B.T.
Found - 24" B.Oak bears S.20°W., 25 lks., old blazes rotted out.
19" B.Oak bears S.20°E., 71 lks., down, BT legible.
B.Oak bears N.50°E., down & rotten.
B.Oak bears N.70°W., 26 lks., small part of stump left.

Intersection fences south and west, old fence corner post down.

Set - 3/4" x 36" Iron rod for corner, from which
10" Cedar bears S.81°E., 81.2 ft., with a brass disc mkd. C.S.
7" Cedar bears N.67½°E., 84.7 ft.
10" Fir bears N.74°W., 74.9 ft.
30" Fir bears S.31½°W., 16.2 ft. with brass disc mkd. County Surveyors Office XI, XII, XIII, XIV.

Doug. County Surveyors Office - Milo E. Godfrey, Deputy - Vern Tracy; Mike Stone - Dec. 1962-Jan. 1963 - C.S. File 49/129-10

Found - 3/4" Iron rod at corner.
34" Fir S.31½°W., 16.2 ft. blaze healed over, tree alive.

(Cont. Next Page)

