TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, Under Contract #57 dated April 12, 1855 - (DCSO records, Volume 11 Page 4602)

Set ¼ sec. post, from which
A B.Oak 12" dia., bears S.57°E., 100 lks. dist.
A W.Oak 16" dia., bears S.70°W., 113 lks. dist.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - March/April 1966 - C.S. File 54/23-26

Found - Orig. 16" now 36", S.70°W., 74.6 ft. Chop open & find "4S" scribe & reverse. Ring count 100+ years.
Stump hole at approx. location of SE BT.
Set brass cap at cor. mkd: County Surveyor's Office, 1966
T26S R7W ¼ S 2|S 1
New BTs - 18" D.Fir N.61°E., 6.7 ft. mkd. ¼ S1 CS BT.
16" B.Oak N.23°W., 7.1 ft. mkd. ¼ S2 CS BT.
Corner lies 10 ft. East of old road not used for number of years.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/3/1994 (added 7/11/2016) - C.S. 64/52-1

Found - 2½" brass cap (properly mkd) on a 1½" O.D. iron pipe protruding 7" above ground.
16" now 34" dia., down W.Oak with a previously opened blaze, no scribing visible, root hole bears S.70°W., 74.6 ft. (agrees with rec.) Orig BT.
18" now 29" dia, D.Fir with a fully healed single blaze, bears N.61°E., 6.7 ft. (agrees with rec) 1966 DCSO (tree to be cut in near future)
16" now 24" dia., 2 ft. high B.Oak stump with scribing. Fd "BT" bears N.23°W., 7.1 ft. (agrees with rec) 1966 DCSO
New - 6" dia., D.Fir double blazed and scribed "¼ S2 CS BT" bears N.54½°W., 30.6 ft.
9" dia., W.Oak double blazed & scribed "¼ S1 CS BT" base of scribed trunk bears S.6°E., 15.1 ft.
6" dia., D.Fir double blazed and scribed "¼ S2 CS BT" bears S.43°W., 41.4 ft.
4" dia., D.Fir double blazed & scribed "X BT" bears S.65°E., 33.0 ft.
Compass decl. 17¾°E.

Fd. ok by D. Edwards 8/2016 - M172-38