TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April, 12 1855 (DCSO records, Volume 11 Page 4596)

Set ¼ sec. post, from which
A B.Oak 20" dia., bears N.17°E., 84 lks. dist.
A B.Oak 10" dia., bears S.17°W., 30 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; S.A. Bilow - Jan. 9, 1959 - C.S. File 49/129-1

Found - Orig. 20" now 32" B.Oak snag N.17°E., 55.4 ft. I open & find good scribing "BT".
Orig. 10" now remains only of SW BT. I find good scribing, "BT" on sec. near fence, checks bearing & distance to old stump hole.
Set brass cap at cor. mkd: ¼ S25/S36 T26S R7W County Surveyor's Office, 1959.
New BTs - 8" Laurel bears N.53°W., 26.0 ft. scribed ¼ S25CSBT
7" R.Fir bears S.65°E., 18.5 ft. scribed ¼ S36 CSBT
This BT in E-W fence line.

Fd. BC by Neil Hibbs, M155-38 - 09/2007
Fd. BC by Neil Hibbs, M168-60 - 10/2014