

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 864080

PRIMARY CORNER DESCRIPTION M.C. So. Bdy. Sec. 13 (Left Bank)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original Dennis Hathorn, under Contract #57 dated April 12, 1855 - (DCSO records, Volume 11 Page 4599)

Set Meander post on left bank of river, from which
A W.Oak 20" dia., bears S.73°W., 28 lks. dist.
A B.Oak 15" dia., bears N.72°W., 135 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; Clete Putnam - May, 1960 - C.S. File 52/36

Found - Orig. 15" now 27" B.Oak N.72°W., 89.1 ft. I open
& find good scribing "T".

Orig. SW BT gone.

Meander Corner is in flood area. We set Witness Corner 40 ft.
West of true corner.

Set Brass cap at cor. mkd. County Surveyors's Office, 1960

Wit. Cor. 40' East to M.C. S 13/ T 26 S R 7 W

S 24/

New BTs - 11" W.Oak bears N.52°W., 12.0 ft. scribed WC MC
S13 CS BT.

12" W.Oak bears S.85°W., 41.0 ft. scribed WC MC
S24 BT.