

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T26-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4647)

-----  
Set ¼ post, 3 ft. long, 3" sq., from which  
A Fir 42" dia., bears S.80°E., 32 lks. dist.  
A Fir 36" dia., bears N.45°W., 30 lks. dist.

GLO resurvey by John W. Meldrum, Deputy Surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4719)

-----  
Set Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which  
A Chinquapin 11" dia., bears S.38°E., 16 lks. dist. mkd. ¼ S BT.  
A Fir 13" dia., bears S.34°W., 37 lks. dist. mkd. ¼ S BT.  
From this cor., the old ¼ sec. cor., which is a point witnessed by the Fir BT on S.80°E., the post and other BT hving been destroyed by fire, bears N.21°45'W., 69 lks. dist. I destroy all marks of the old cor. on the remaining BT of the original survey.

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - July 13, 1977 - C.S. file 58/139 and M 66-12

-----  
Set by single proportion, a 2" Brass cap monument, from which  
An 18" Hemlock bears N.81°W., 12.8 ft. scribed ¼ Cor RP.  
A 13" Hemlock bears S.85½°E., 19.1 ft. scribed ¼ Cor RP.