TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; and 25, T26-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4647)

Set ¼ sec. post, 3 ft. long, 3" sq., from which
A Fir 50" dia., bears S.85°W., 6 lks. dist.
A Fir 36" dia., bears S.40°E., 50 lks. dist.

GLO resurvey by John W. Meldrum, Deputy Surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4720-21)

Set Fir post 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 36" dia., bears S.76°E., 232 lks. dist. mkd. ¼ S BT.
A Fir 36" dia., bears S.68°W., 127 lks. dist. mkd. ¼ S BT.
After diligent search, I failed to find the old ¼ sec. cor.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14176)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 25 S 30
T 26 S
R 9 W R 8 W
1967
from which
A Fir 11" dia., bears N.76°E., 11½ lks. dist. mkd. ¼ S30 BT.
A Fir 10" dia., bears S.61°W., 17 lks. dist. mkd. ¼ S25 BT.