

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T26-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4647)

-
- Set Cedar post 4 ft. long, 4" sq., from which
- A Fir 40" dia., bears N.45°E., 36 lks. dist.
 - A Fir 36" dia., bears N.30°W., 75 lks. dist.
 - A Fir 36" dia., bears S.35°W., 28 lks. dist.
 - A Fir 40" dia., bears S.53°E., 72 lks. dist.

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4721)

Set Laurel post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 19, 24, 25 and 30, marked T26S S19 on NE.; R8W S30 on SE.; S25 on SW.; and R9W S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which

- A Fir 40" dia., bears N.30°30'E., 47 lks. dist. mkd. T26S R8W S19 BT.
- A Fir 40" dia., bears S.62°E., 155 lks. dist. mkd. T26S R8W S19 BT.
- A Fir 50" dia., bears S.40°30'W., 93 lks. dist. mkd. T26S R9W S25 BT.
- A Fir 36" dia., bears N.43°15'W., 50 lks. dist. mkd. T26S R9W S24 BT.

From this cor., the old cor. which is a Cedar post witnessed as described by the surveyor general, bears S.3°23'W., 10.02 chs. dist. I destroy the post, which is still standing but much decayed and obliterate the marks from the old BTs.

Fd. GLO resurvey by Wm Heydon Dep Surveyor under contract No. 656, dated May 21, 1896 - (DCSO recs Vol 11 Page 4699)

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14176-77)

-
- The Sec. Cor., determined from the original bearing trees:
- A burned Fir stump 34" dia., bears N.30½°E., 47 lks. dist., with no marks remaining.
 - A Fir 65" dia., bears S.52°E., 160 lks. dist., with fragmentary scribe marks visible on weathered bark blaze. (Rec. S.62°E., 155 lks.)
 - A Fir 65" dia., bears S.40½°W., 93 lks. dist., with healed blaze.
 - A Fir 48" dia., bears N.43¼°W., 50 lks. dist., with scribe marks T26S R9 S BT visible on weathered bark blaze.

(Cont. Next Page)

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T26-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 12" in the ground,
to solid rock, and in a mound of stone, 3 ft. base, to top,
with brass cap mkd:

T 26 S	
R 9 W	R 8 W
<u>S 24</u>	<u>S 19</u>
S 25	S 30
1967	

from which a new bearing tree
A Fir 65" dia., bears N.16°E., 9 lks. dist. mkd. T26S R8W
S19 BT.

From this point United States Coast and Geodetic Survey
triangulation station ELWOODS 1953, bears S.67°51'E., 18.61
chs. dist., monumented with a standard brass cap, 3½" dia.,
firmly set in a concrete post, 10" dia., extending 8" above
ground, with top marked ELWOODS 1973, and a triangle.