

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4700)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A chinquapin, 5" dia., bears N.6°W., 148 lks., mkd: ¼ S BT
A willow, 5" dia., bears S.76½°E., 165 lks., mkd: ¼ S BT.

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14185-6)

Point for the ¼ sec. cor. of secs. 19 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

¼ $\frac{S\ 19}{S\ 30}$
T26S R8W
1967

from which

A fir, 25" dia., bears N.33°W., 40 lks., mkd: ¼ S19 BT.
A fir, 25" dia., bears S.58°E., 56 lks., mkd: ¼ S30 BT.