

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4694)

Set yew post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 36" dia., bears N.42°E., 52 lks., mkd: ¼ S BT.
A hemlock, 6" dia., bears N.57°W., 23 lks., mkd: ¼ S BT.

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14179)

The ¼ sec. cor. of secs. 31 & 32 determined at the record bearing & distance from each of the orig. BTs:

A fir snag, 44" dia., bears N.47°E., 52 lks., with healed blaze. (Rec. N.42°E.)
A hemlock, 14" dia., bears N.67°W., 23 lks., with scribe marks ¼ S visible on opened blaze. (Rec. N.57°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼
S 31|S 32
T26S R8W
1967

from which new BTs

A hemlock, 14" dia., bears S.50°E., 40 lks., mkd: ¼ S32 BT
A hemlock, 15" dia., bears N.60°W., 57 lks., mkd: ¼ S31 BT