

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page 4694)

-----  
Set cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 29, 30, 31, & 32, 200 ft. below Callahan Trail, mkd T26S S29 on NE, R8W S32 on SE, S31 on SW & S30 on NW faces with 1 notch on S and 5 on E edges, from which

A fir, 30" dia., bears N.64°E., 198 lks., mkd: T26S R8W S29 BT.

A yew, 16" dia bears S.11°E. 90 lks mkd: T26S R8W S32 BT  
No living trees in secs. 30 & 31.

Dig pits 18x18x12, 5½ ft. from post, in those secs. and raised mounds of earth NW & SW from said cor. to secs. 30, 29, 31, & 32, in secs. 30 & 31.

GLO survey by Wm Heydon, Dep Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Pg 4718-9)

-----  
Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:

At the corner of secs. 29, 30, 31, & 32, I dig new pits, 18x18x12" in each sec. 5½ ft. from corner & raised a mound of earth, 2 ft. base, 1½ ft. W of cor.

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14180)

-----  
Point for the cor. of secs. 29, 30, 31, & 32, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked:

T26S R8W  
S 30|S 29  
S 31|S 32  
1967

from which

A fir, 15" dia bears N.73°E. 36 lks mkd: T26S R8W S29 BT

A fir, 15" dia bears S.39°E. 51 lks mkd: T26S R8W S32 BT

A fir, 15" dia bears S.14°W. 26 lks mkd: T26S R8W S31 BT

A fir, 20" dia bears N.43°W. 46 lks mkd: T26S R8W S30 BT