

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4697)

-----

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which

- A chinquapin, 4" dia., bears N.58°E., 23 lks., mkd: ¼ S BT
- A chinquapin, 5" dia., bears N.48°W., 17 lks., mkd: ¼ S BT

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14184-5)

-----

Point for the ¼ sec. cor. of secs. 29 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

¼  
S 30|S 29  
T26S R8W  
1967

from which

- A fir, 10" dia., bears N.27°E., 32 lks., mkd: ¼ S29 BT.
- A fir, 14" dia., bears S.75°W., 31½ lks., mkd: ¼ S30 BT.