

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4697-8)

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 19, 20, 29, & 30, mkd T26S S20 on NE, R8W S29 on SE, S30 on SW & S19 on NW faces with 2 notches on S and 5 on E edges, from which
A maple, 5" dia., bears N.63°E., 96 lks., mkd: T26S R8W S20 BT.
A fir, 8" dia., bears S.6°E., 175 lks., mkd: T26S R8W S29 BT.
A cedar, 20" dia., bears S.52°W., 210 lks., mkd: T26S R8W S30 BT.
A maple, 5" dia., bears N.29°W., 40 lks., mkd: T26S R8W S19 BT.

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14185)

The cor. of secs. 19, 20, 29, & 30, determined at the record bearing & dist. from the only remaining orig. BT:
A cedar snag, 25" dia., bears S.52°W., 210 lks., with scribe marks 30 T26S W BT visible on open & burned blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 10" in the ground, to solid rock & in a mound of stone, 4 ft. base, to top, with brass cap marked:
T26S R8W
S 19|S 20
S 30|S 29
1967
from which new BTs
A fir, 22" dia. bears N.58°E. 25 lks. mkd: T26S R8W S20 BT
A fir, 20" dia. bears S.75°E. 65 lks. mkd: T26S R8W S29 BT
A fir, 18" dia. bears S.27°W. 14 lks. mkd: T26S R8W S30 BT
A fir, 22" dia. bears N.31°W. 21 lks. mkd: T26S R8W S19 BT

Fd. & used on BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14871-2)

cont. next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tony Hostetter - For: Weyerhaeuser Co. - May 2001 - C.S. File 65/37-12 & 13

Found: No evidence of 1972 BLM brass cap or BTs described on pgs. 14868-9 of DCSO recs. However, blazed lines were found in 4 directions from this corner & used to establish approx. location of 1972 mon. (Note: this area has been subject to landslide & flood damage.) From this approx. point, a steel fence post was found buried lying horizontally @ N.70°W., 8 ft. away. There is also a large rock @ N.60°E., 24 ft. more or less buried under several large logs which may be the orig. bearing object described by the BLM in 1972. The ¼ corner between secs. 20 & 29 measured by 1972 BLM retracement survey to be 40.40 ch (2666.40 ft.), N.88°45'W., from this sec. corner, was found to be 2664.92 ft. from the approx. corner position (as measured by total station traverse).

In order preserve this approx. location, which may be the best available of an orig. corner position, the following BTs were established:

- 20" Alder, bark scribed "S21 SW BT" WEYCO tag, bears N.8°E., 29.4 ft. to spike placed in root collar below scribing.
- 22" Alder, bark scribed "S21 SW BT" WEYCO tag, bears N.20°E., 48.3 ft. to spike placed in root collar below scribing.
- "X" marked in sandstone bluff, bears S.70°W., 22.7 ft.