

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4701)

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 17, 18, 19, & 20, mkd T26S S17 on NE, R8W S20 on SE, S19 on SW & S18 on NW faces with 3 notches on S and 5 on E edges, from which
A hemlock, 16" dia., bears N.68°E., 50 lks., mkd: T26S R8W S17 BT.
A cedar, 10" dia., bears S.62°E., 17 lks., mkd: T26S R8W S20 BT.
A hemlock, 18" dia., bears S.72°W., 30 lks., mkd: T26S R8W S19 BT.
A hemlock, 12" dia., bears N.70½°W., 22 lks., mkd: T26S R8W S18 BT.

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-12

FD. 11/1967 By Williams - Lester
Witnessed by: Pipe
OBT 30" Hemlock N.75°E., 32.3 ft. "W" nail.
OBT 16" Cedar S.58°E., 13.0 ft. "W" nail.
OBT? 30" Hemlock S.63°W., 19.5 ft. "W" nail.
OBT 24" Hemlock N.67°W., 12.0 ft. "W" nail.

BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14873-4)

The corner of secs. 17, 18, 19, & 20, determined from the orig. BTs:
A hemlock, 23" dia., bears N.72°E., 50 lks., with partial scribe marks visible on opened blaze. (Rec. N.68°E.)
A cedar, 20" dia., bears S.62°E., 22 lks., with scribe marks 26 visible on opened blaze. (Rec. 17 lks.)
A hemlock, 33" dia., bears S.72°W., 30 lks., with scribe marks visible on opened blaze.
A hemlock, 25" dia., N.70½°W., 18 lks., with partial scribe marks visible on opened blaze. (Rec. 22 lks.)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T26S R8W
S 18 | S 17
S 19 | S 20
1972