

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4708)

-----

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 5, 6, 7, & 8, mkd T26S S5 on NE, R8W S8 on SE, S7 on SW & S6 on NW faces with 5 notches on S & E edges, from which

- A fir, 36" dia. bears N.69½°E. 64 lks. mkd: T26S R8W S5 BT
- A fir, 30" dia., bears S.21°12'E., 66 lks., mkd: T26S R8W S8 BT.
- A fir, 30" dia. bears S.19°W., 18 lks. mkd: T26S R8W S7 BT
- A fir, 30" dia., bears N.42°W., 4 lks. mkd: T26S R8W S6 BT

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-3

-----

- FD. 4 BTs - 10/1961 - Reppeto - Stevens
- 6" DF, N.89°E., 33.4 ft. "W" nail tag.
  - 8" DF S.48½°E., 35.8 ft. "W" nail tag.
  - 8" DF S.09°W., 9.2 ft. "W" nail tag.
  - 8" DF N.38¾°W., 14.9 ft. "W" nail tag.