

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & 5, T27-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4643)

-----  
Set Fir ¼ post 3 ft. long, 3" sq., from which  
A Fir 42" dia., bears S.60°E., 23 lks. dist.  
A Fir 48" dia., bears N.15°E., 5 lks. dist.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14174)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:  
T 26 S R 8 W  
¼ S 32  
S 5  
T 27 S  
1967

from which  
A Hemlock 10" dia., bears N.11°E., 49 lks. dist. mkd. ¼ S32 BT.  
A Hemlock 9" dia., bears S.22°E., 43 lks. dist. mkd. ¼ S5 BT.