

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4695)

Set myrtle post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A myrtle, 4" dia., bears N.88°W., 600 lks., mkd: ¼ S BT.
(Out of limit)
A laurel, 6" dia., bears N.85°E., 575 lks., mkd: ¼ S BT.
(Out of limit)
Dig pits, 18x18x12, 5½ ft. SW & NE of post & raised mound of earth W of post.

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14181)

Point for the ¼ sec. cor. of secs. 29 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
¼ S 29
 S 32
T26S R8W
1967

from which
A fir, 28" dia., bears N.45°E., 38 lks., mkd: ¼ S29 BT.
A fir, 15" dia., bears S.56°E., 35 lks., mkd: ¼ S32 BT.