

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4698-9)

Set a fir post, 3 ft. long, 4" sq., in a stone mound, 3 ft. base, 18" high, with a stone marked thus: (X) on a rocky ridge, for ¼ sec. cor. mkd ¼ S on N face, from which
Raised a stone mound, NW & SW 8 ft. from cor.
Impracticable to dig pits.
Also marked nearest trees:
A fir, 16" dia., bears N.18°W., 21 chs., mkd: ¼ S BT.
A maple, 4" dia., bears S.4°W., 22.08 chs., mkd: ¼ S BT.

BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14871)

Point for the ¼ sec. cor. of secs. 20 & 29, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
T26S R8W
¼ S 20
 S 29
 1972
from which
A fir, 33" dia., bears N.43°E., 82 lks., mkd: ¼ S20 BT.
A hemlock, 13" dia. bears S.61½°E., 54½ lks. mkd: ¼ S29 BT
Set a 5 ft. steel fence post alongside iron post.

Tony Hostetter - For: Weyerhaeuser Co. - May 2001 - C.S. File 65/37-12 & 13

Found - 1972 BLM BC as described in DSCO recs pg. 14871.
33" Fir, face evident, BLM BT, bears N.43°E., 54.1 ft. to center.
New BTs- 16" Alder, bark scribed "S20 ¼ BT", WEYCO tag, bears N.20°E., 18.2 ft. to spike placed in root collar below scribing.
26" Fir, scribed "S29 ¼ BT" WEYCO tag, bears S.20°W., 41.1 ft. to spike placed in root collar below scribing.
22" Fir, scribed "S29 ¼ BT" WEYCO tag, bears S.66°W., 11.6 ft. spike placed in root collar below scribing.

Fd as per 2001 record. by T Hostetter, 7-2017, M173-54