

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4683)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 28, 29, 32, & 33, 300 ft. below point at 60 chs. mkd T26S S28 on NE, R8W S33 on SE, S32 on SW & S29 on NW faces with 4 notches on E and 1 on S edges, from which

~~A fir, 28" dia., bears N.47°E., 400 lks., mkd: T26S R8W S28 BT. (Out of limit)~~

~~A fir, 14" dia. bears S.40°E. 33 lks. mkd: T26S R8W S33 BT~~

~~A fir, 30" dia., bears S.18°W., 317 lks., mkd: T26S R8W S32 BT. (Out of limit)~~

~~A fir, 43" dia. bears N.10°W. 29 lks. mkd: T26S R8W S29 BT~~

Dig pits in secs. 28 & 32 18x18x12, 5½ ft. and raised a mound of earth 4 ft. base 2 ft. high, W of cor.

Note on side of page of orig. line notes "see page 8 of correction notes" Page 8 of correction notes equals page 4718 of our typed notes 10/2/2006 JC DCSO

GL0 survey by William P Heydon, Dep Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Pg 4718)

Correction of surveys as ordered by the Commissioner of the GL0 under date of March 18, 1898:

I find the witness trees at the cor. of secs. 28,29, 32 & 33 destroyed by fire and therefore made new ones as follows:

A fir, 12" dia. bears N.50°E., 4 lks. mkd: T26S R8W S28 BT

A fir, 10" dia. bears S.52°E. 65 lks. mkd: T26S R8W S33 BT

A fir, 14" dia. bears S.57°W., 8 lks. mkd: T26S R8W S32 BT

A fir, 10" dia. bears N.49°W. 33 lks. mkd: T26S R8W S29 BT

Marvin C Ramsey - For: J.H. Baxter - July 1960 - C.S. 51/41-2

Det. from OBT's:

12" D.Fir Snag bears N.50°E. 4 lks. w/partial scribe mks.

10" D.Fir bears S.52°E. 65 lks., down and decayed.

14" D.Fir bears S.57°W. 8 lks., down and decayed.

10" D.Fir Snag bears N.49°W. 33 lks. with axe mks., ether mks. destroyed by fire.

Set an Iron Pipe 3' long 2" in dia., 28" in the ground mid. R5404 from which new bearing trees:

6" D.Fir bears N.64°E., 10 lks. mkd. T26S R8W S28 RS404 BT

18" D.Fir bears S.10°E. 21 lks. mkd. T26S R8W S33 RS404 BT

10" D.Fir bears S.77½°W. 9 lks. mkd. T26S R8W S32 RS404 BT

12" D.Fir bears N.33°W. 19 lks. mkd. T26S R8W S29 RS404 BT

continued next page

1

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group No. 638, surveyed May/July 1967 - (DCSO Records Vol. 34 Page(s) 14178-9)

The cor. of secs. 28, 29, 32, & 33, perpetuated & recorded by Ramsey, in 1960, with an iron pipe, 36" long, 2" dia., firmly set 28" in the ground, from which the only remaining orig. BT
A rotted fir stump, 16" dia., bears N.50°E., 4 lks. with fragmentary scribe marks visible on opened blaze.

and trees marked by Ramsey
A fir, 8" dia., bears N.64°E., 11 lks., with scribe marks
T26S R8 S28 RS404 BT visible on partially healed blaze.
A fir, 18" dia., bears S.10°E., 21½ lks. with healed blaze
A fir, 10" dia., bears S.77°W., 9 lks., with scribe marks
T26S R8W S32 RS404 BT visible on partially healed blaze
A fir, 13" dia., bears N.33°W., 19 lks. with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T26S	R8W
S 29	S 28
S 32	S 33
1967	

Deposit the iron pipe alongside the iron post.