

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4684-5)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec cor. 150 ft above sec. cor. mkd ¼ S on W face, from which
A madrona, 6" dia., bears N.81°W., 200 lks., mkd: ¼ S BT.
A myrtle, 4" dia., bears S.8°E., 170 lks., mkd: ¼ S BT.

Marvin C Ramsey - For: J.H. Baxter - July 1960 - C.S. 51/41-2

Set at proportionate distance. Find no evidence of the Orig. Corner.
Set an Iron Pipe 3' long, 1½" dia., 28" in the ground mkd. RS404, from which:
22" D.Fir bears N.37°E., 46 lks. mkd. ¼ S28 RS404 BT.
26" D.Fir bears S.24°W., 37 lks. mkd. ¼ S29 RS404 BT.