

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4685)

An X cut on rock at the true point for cor. to secs. 20, 21, 28, & 29. Where I erect a mound of rock, 3 ft. base & 1½ ft. high, from which

- An X cut on same rock, bears N.60°E., 40 lks.
- Raised a mound of rock, S.45°E., 25 lks.
- An X cut on same rock upon which cor. stands, bears S.18°W., 26 lks.
- Raised mound of rock N.45°W., 25 lks.

Pits impracticable & no living timber suitable for BTs, within limits.

Marvin C Ramsey - For: J.H. Baxter - July 1960 - C.S. 51/41-2

This corner falls on bedrock in the bed of a stream.

Set - An iron pipe 3' long, 2" in dia, on bedrock with a mound of stone to the top, mkd. RS404, from which the only original evidence of this corner is an X mkd. on the rock bears N.60°E., 40 lks. A prominent rock bears S.18°W., 26 lks., but I am unable to find the X.

New - 12" W.Fir bears N.67½°E. 59 lks. mkd. T26S R8W S21 RS404, BT.

- 8" Cedar bears S.82½°E. 48 lks. mkd. T26S R8W S28 RS404 BT.
- 8" Hemlock bears S.42½°W. 42 lks. mkd. T26S R8W S29 RS404 BT
- 18" Alder bears S.18½°W. 56 lks. mkd. T26S R8W S20 RS404 BT

BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14868-9)

Corner of secs. 20, 21, 28, & 29, perpetuated & recorded by Ramsey, in 1957 from which the remaining orig bearing object:

- A basalt boulder 8 ft. x 6 ft. x 4 ft., above ground, bears N.60°E., 40 lks., mkd. X on W face.

and trees marked by Ramsey

- A root hole, bears N.67½°E., 59 lks., with a down fir alongside, 14" dia. with illegible scribe marks on root blaze.
- A cedar snag, 8" dia., bears S.82½°E., 48 lks., with scribe marks T26S R8W S28 RS404 BT visible on open blaze.

continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A hemlock, 8" dia., bears S.42½°W., 42 lks., with scribe marks T26S R8W S29 RS 404 BT visible on open blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 20" in the ground, and in a mound of stone, 36" base to top, with brass cap marked:
T26S R8W
S 20 | S 21
S 29 | S 28
1972
from which new bearing objects
A basalt boulder, 4 ft. x 3 ft. x 2 ft., bears S.50°E., 85 lks., mkd. XBO on NW face.
A basalt boulder, 6 ft x 4 ft. x 4 ft., bears N.53°W., 44½ lks., mkd. XBO on SE face.
No suitable trees available within limits.
Set a 5 ft. steel fence post alongside iron post.