TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4686)

Enter green timber, set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 20" dia., bears N.18°E., 40 lks., mkd: ¼ S BT.
A fir, 17" dia., bears N.40°W., 67 lks., mkd: ¼ S BT.

BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14869)

Point for the ¼ sec. cor. of secs. 20 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked: T26S R8W

¼
S 20 | S 21
1972

from which
A hemlock, 13" dia., bears S.72°E., 77 lks., mkd: ¼ S21 BT
A hemlock, 11" dia., bears S.10°W., 67 lks., mkd: ¼ S20 BT

Tony Hostetter - For: Weyerhaeuser - 7/2017 - M173-54

Found - 1972 BLM brass cap, 4" out of ground as described by Jelly and Bowder (DSCO records Volume 36, Pg 14869.
1972 BTs Are gone. Steel fence post 1' west.
New BTs- 25" Hemlock, scribed "S21 ¼ BT", BT tag, bears N.38°E., 40.4 ft to spike.
19" Hemlock, scribed "S21 ¼ BT", BT tag, bears S.33°E., 9.5 ft to spike.
20" Hemlock, scribed "S20 C¼ BT", BT tag, bears S.84°W., 46.5 ft to spike. 21" Cedar, scribed "S20 C¼ BT" BT tag bears N.59°W. 39.1 ft to spike

---