

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm P. Heydon, Dep Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Pages 4686-7)  
-----

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 16, 17, 20, & 21, mkd T26S S16 on NE, R8W S21 on SE, S20 on SW & S17 on NW faces with 3 notches on S and 4 on E edges, from which  
 A maple, 7" dia. bears N.81°E. 80 lks mkd: T26S R8W S16 BT  
 A hemlock, 14" dia., bears S.83°E., 109 lks., mkd: T26S R8W S21 BT.  
 A fir, 24" dia. bears S.10°W. 125 lks mkd: T26S R8W S20 BT  
 A hemlock, 6" dia bears N.60°W. 7 lks mkd: T26S R8W S17 BT

---

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-11  
-----

FD. 1/1968 By Holmes-Morgan-McMillan,  
 Cedar post  
 10" Hem. N.40°E., 8.2 - New?  
 18" Fir S.5½°E., 14.6 - New?  
 36" Fir S.10°W., 85.3  
 20" Hem. N.60°W., 4.6

---

BLM resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group No. 763, surveyed April 1972 - (DCSO records Vol. 36 Page(s) 14870)  
-----

The corner of secs. 16, 17, 20, & 21, perpetuated & recorded by Weyerhaeuser Timber Co., in 1968, monumented with a cedar post, 3" dia., firmly set, protruding 18", above the ground, from which the remaining original BTs:  
 A fir, 45" dia., bears S.10°W., 130 lks w/scribe marks S20 T26S R8W BT vis on bark blaze (Rec & to face 125 lks)  
 A hemlock, 21" dia., bears N.60°W., 7 lks., with partial scribe marks visible on open blaze.  
 and trees marked by Weyerhaeuser in 1968  
 A hemlock, 11" dia., bears N.41°E., 12 lks. w/scribe marks T26S R8W S16 BT visible on opened blaze, & a galvanized nail with "W" embossed on head driven in base of tree.  
 A fir, 22" dia., bears S.7¼°E., 22 lks., with scribe marks T26S R8W S21 BT visible on opened blaze, & a galvanized nail with "W" embossed on head driven in base of tree.

At the corner point  
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:  
 T26S R8W  
 S 17 | S 16  
 S 20 | S 21  
 1972

cont.

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Tony Hostetter - For: Weyerhaeuser Co. - May 24, 2019 - C.S.  
File 65/102-66

-----

Found - 1972 BLM brass cap as described DSCO records VOL 36,  
PG 14870. from which:  
22" Fir snag, scribing visible, "W" nail, bears;  
S.07°E., 14.5 ft to center.  
New BTs- 12" Fir, marked "X", BT tag, bears; N.78°E., 16.7 ft  
to 6" spike.  
12" Fir, marked "X", BT tag, bears; S.79°42'E., 19.8  
ft to 6" SPIKE.  
11" Fir, marked "X", BT tag, bears; S.47°43'E., 18.2  
ft to 6" spike.  
10" Fir, marked "X", BT tag, bears; S.90°W 0.2 ft to  
6" spike.