

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4691)

Set yew post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 4, 5, 8, & 9, mkd T26S S4 on NE, R8W S9 on SE, S8 on SW & S5 on NW faces with 4 notches on E and 5 on S edges, from which

- A fir, 20" dia. bears N.40°E., 50 lks. mkd: T26S R8W S4 BT
- A maple, 5" dia. bears S.36°E., 5 lks. mkd: T26S R8W S9 BT
- A fir, 30" dia. bears S.38°W., 52 lks. mkd: T26S R8W S8 BT
- A madrona, 10" dia., bears N.29°W., 20 lks., mkd: T26S R8W S5 BT.

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-2

FD. 5/1963 - Stevens & Party

Check by Post & mks.

- OBT 20" Fir "W" nail, tag, N.47°E., 31.3 ft.
- 8" W.Cedar, "W" nail, tag, S.08°E., 21.5 ft. - New?
- OBT 36" Fir, "W" nail, tag, S.38°W., 30.0 ft.
- OBT 10" Madrone, "W" nail, tag, N.29°W., 12.2 ft.