

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T25-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3932)

 Cor. to secs. 4, 5, 32 and 33, Set Cedar post 4 ft. long,, 4" sq., from which

- A Hemlock 24" dia., bears S.60°E., 20 lks. dist.
- A Cedar 8" dia., bears S.60°W., 23 lks. dist.
- A W.Fir 26" dia., bears N.55°W., 27 lks. dist.
- A Cedar 8" dia., bears N.20°E., 38 lks. dist.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3978-79)

 The Sec. Cor., which is a badly decayed post, mkd. and witnessed as described by the Surveyor General. I reestablish as follows: I destroy old cor., and at exact point, Set a Fir post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 4, 5, 32 and 33, mkd. T25S S33 on NE.; R8W S4 on SE.; T26 S5 on SW.; and S32 on NW. faces; with 4 notches on E. and 2 notches on W. edge, from which

- A Fir 40" dia., bears N.60°E., 23 lks. dist. mkd. T25S R8W S33 BT.
- A Fir 40" dia., bears S.85°E., 81 lks. dist. mkd. T26S R8W S4 BT.
- A Fir 45" dia., bears S.15°W., 10 lks. dist. mkd. T26S R8W S5 BT.
- A Hemlock 40" dia., bears N.45°W., 32 lks. dist. mkd. T25S R8W S32 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/72-17

 Found - Orig. 8" Cedar now 20" snag, decayed center, S.60°W., 15.2 ft., no scribing found.
 Orig. 8" now 24" Cedar, alive, N.20°E., 25.1 ft., open and find "S33" scribe and reverse.
 Only decayed remains of NW. orig. BT.
 No trace SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T25S	R8W	S 32	S 33
T26S		S 5	S 4

 1968

New BTs- 20" Cedar N.24°W., 26.6 ft. mkd. T25S R8W S32 CSBT
 9" Hemlock N.34°E., 12.2 ft. mkd. T25S R8W S33 CSBT
 7" Hemlock S.9°E., 21.8 ft. mkd. T26S R8W S4 CS BT.
 9" Hemlock S.40°W., 23.9 ft. mkd. T26S R8W S5 CS BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Corner lies on moderate easterly slope approx. 100 ft. West of bench, course N. and S.

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-3 - added 3/14/2019)

FD. 9/1962 - Reppeto, Stevens & Party
22" W.Cedar 'W' nail, tag N.20°E., 24.8 ft.
30" D.F. 'W' nail, tag S.27°E., 39.2 ft
18" W.Cedar 'W' nail, tag S.58°W., 15.2 ft
55" D.F. 'W' nail, tag N.55°W., 50.2 ft.

BLM resurvey by James E. Jelley and Jack W. Bowder, Cadastral Surveyors, under Group #767, Surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15037)

The Sec. Cor., perpetuated and recorded by Tracy in 1968, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1968, from which the remains of the original bearing tree:

A sawed Cedar stump 25" dia., bears N.17°E., 38 lks. dist., no marks visible on open blaze. (Rec. N.20°E.) and a bearing tree mkd. by Tracy:

A sawed Cedar stump 20" dia., bears N.24°W., 42 lks. dist., no marks visible.

AND BEARING TREES OF WHICH I HAVE NO RECORD:

A sawed Fir stump 60" dia., bears N.40°E., 77½ lks. dist., with a galv. nail with "W" embossed on head, driven into base.

A sawed Fir stump 36" dia., bears S.54½°E., 149 lks. dist., with a galv. nail with "W" embossed on head, driven into base.

A sawed Fir stump 46" dia., bears S.57°W., 167 lks. dist., with a galv. nail with "W" embossed on head, driven into base.

A sawed Fir stump 60" dia., bears N.57°W., 81½ lks. dist., with a galv. nail with "W" embossed on head, driven into base.

(See also, 1961-62 Weyerhaeuser corner report filed in DCSO, June 17, 1970, C.S. File 55/155A)