

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4685-6)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

 A fir, 7" dia., bears N.45°W., 60 lks., mkd: ¼ S BT.

 A fir, 10" dia., bears S.10½°W., 400 lks., mkd: ¼ S BT.
 (Out of limit)

Raised a mound of rock 10 ft. W of cor. Pit impracticable.

Marvin C Ramsey - For: J.H. Baxter - July 1960 - C.S. 51/41-2

Point for ¼ corner at proportionate dist. No evidence of the original Corner.

Set an Iron Pipe 3' long 1½" in dia. 28" in the ground mkd. RS404 from which:

 16" D.Fir bears N.21°E., 21 lks. mkd. ¼ S21 RS404 BT.

 18" D.Fir bears S.75°E., 14 lks. mkd. ¼ S28 RS404 BT.