

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A. R. and S.C. Flint, Under Contract #392,  
dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3932)

-----  
Set Cedar ¼ post 3 ft. long, 3" sq., from which  
A Hemlock 16" dia., bears S.15°E., 44 lks. dist.  
An Alder 12" dia., bears N.87°E., 4 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Sept. 23, 1968 - C.S. File 54/72-29

-----  
Found - Orig. 16" now 28" Hemlock, S.15°E., 29.0 ft. open  
and find "T" scribe.

No trace of other orig. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T25S R8W ¼ S 33  
T26S S 4

1968

New BTs- 35" Hemlock S.60°W., 33.1 ft. mkd. "¼ S4 CS BT"  
32" Hemlock N.29½°E., 26.0 ft. mkd. "¼ S33 CS BT"

Tony Hostetter - For: Weyerhaeuser Co. - June 9, 2015 - C.S.  
File 65/89-50

-----  
Found - 1968 Douglas Co. Surveyor brass cap as described in  
C.S. file 54/72

28" Hemlock stump, OBT, faint scribing visible,  
bears S.15°E., 29.0 ft. to center.

Rotten Hemlock stump, BT tag, bears S.60°W., 33.1  
ft. to center.

32" Hemlock stump, no visible evidence, bears  
N.29½°E., 26.0 ft. to center.

New BTs- 19" Fir, BT tag, bears N.70°E., 9.0 ft. to 6" spike,  
placed below tag.

24" Fir, BT tag, bears S.15°E., 39.8 ft. to 6"  
spike, placed below tag.

16" Fir, BT tag, bears S.50°W., 4.7 ft. to 6" spike,  
placed below tag.

16" Fir, BT tag, bears N.08°W., 31.0 ft. to 6"  
spike, placed below tag.