

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4672)</p> <p>-----</p> <p>Set a yew post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which</p> <p> A fir, 36" dia., bears N.53°E., 115 lks., mkd: ¼ S BT. (No trees in limit W of line)</p> <p> A fir, 36" dia., bears S.77°E., 125 lks., mkd: ¼ S BT.</p>
<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4716)</p> <p>-----</p> <p>Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:</p> <p>Intersect ¼ sec. cor. I find the distance to the NE bearing tree to this cor. as reported by the Examiner to Wit: 115 lks. dist. instead of 15 lks. as reported in the notes now on file in the U.S. Surveyor General's Office.</p> <p>9/20/2006 - I double checked the orig. line notes & in the 1896 line notes Heydon calls the NE BT as being 115 lks - We do not have any report calling for 15 lks. JC DCSO</p>
<p>Bruce Shaner - For: Hub Lumber Co. - June 24, 1974 - RM 2-63</p> <p>-----</p> <p>Set - Brass cap mkd: T26S R8W WM ¼ S33, S34 1974 from which:</p> <p> 16" D.Fir, I scribed "¼S BT" bears N.56°W., 11.6 ft.</p> <p> 16" D.Fir, I scribed "¼S BT" bears N.28°E., 4.7 ft.</p> <p> No orig. evidence found.</p>
<p>Dependent resurvey by John P. Farnsworth, Cadastral Surveyor, under Group No. 1065, surveyed June/July 1981 - (DCSO Records Vol. 44 Page(s) 17036-7)</p> <p>-----</p> <p>The ¼ sec. cor of secs. 33 & 34, established by proportionate measurement & recorded by Shaner, in 1974, & accepted as the best available evidence of the position of the orig. cor., monumented with an iron post, 1½" dia. firmly set, projecting 6", above ground, with brass cap(properly) mkd.</p> <p>from which BTs mkd by Shaner</p> <p> A fir, 19" dia., bears N.28°E., 7 lks., with illegible scribe marks visible on partially healed blaze.</p> <p> A fir, 18" dia., bears N.56°W., 18 lks., with illegible scribe marks visible on partially healed blaze.</p>
<p>FD. Ok 7/1990 - C.S. 63/127-32</p>