

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4674-5)

-----  
Set fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 21, 22, 27, & 28, mkd T26S S22 on NE, R8W S27 on SE, S28 on SW & S21 on NW faces with 3 notches on E and 2 notches on S edges, from which  
A fir, 30" dia. bears N.43°E. 36 lks. mkd: T26S R8W S22 BT  
A fir, 40" dia. bears S.40°E. 91 lks. mkd: T26S R8W S27 BT  
A fir, 30" dia. bears S.44°W. 40 lks. mkd: T26S R8W S28 BT  
A fir, 48" dia. bears N.56°W. 87 lks. mkd: T26S R8W S21 BT

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4717)

-----  
Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:  
The sec. cor. to secs. 21, 22, 27 & 28 is found as described by the Examiner. I supply the omitted markings as follow: T26S on NE, R8W on SE & 2 notches on S & 3 notches on E edges, from which the BTs are as originally recorded.

Marvin C. Ramsey - For: J.H. Baxter - Aug 1959 - C.S. 51/41-1

-----  
Determined from the only extant bearing tree that can be identified, the other BTs are badly burned:  
Set - An Iron Pipe 3' long, 2" dia., 28" in the ground, mkd. RS404 from which the only extant original BT:  
32" Fir Snag bears N.43°E. 36 lks. w/partial scribe mks  
New - 8" Chinquapin bears N.8¾°E., 31 lks. mkd. T26S R8W S22 RS404 BT.  
16" Fir bears S.55¾°E. 46 lks mkd T26S R8W S27 RS404 BT  
22" Fir bears S.15°W. 70 lks. mkd T26S R8W S28 RS404 BT  
9" Chinq. bears N.61¾°W. 43 lks. mkd. T26S R8W S21 RS404 BT.

Fd. Ok 8/1985 - Michael McDowell, Weyerhaeuser. M99-18