TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4676)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 8" dia., bears N.51°E., 88 lks., mkd: ¼ S BT.
A fir, 8" dia., bears N.44°W., 90 lks., mkd: ¼ S BT.

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4717)

Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:
Found the ¼ sec. cor. as reported by the Examiner. I erase the markings on the N face and mark ¼ S on W face. The distance to the NE BT is 88 lks. as reported by the examiner instead of 78 lks as reported in original notes.

Triangle Engineering Co. Nick Juliano - May 1972 - M44-79 & C.S. File 55/251

Found no evidence of 8"Fir BT.
Set - 1½" Iron pipe with brass cap. Referenced with "W" nails and plates.
New BTs- 24" Fir, S.25°E., 47.3 ft.
32" Fir, N.04°W., 54.5 ft.