

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4678)</p> <p>-----</p> <p>Set a fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which</p> <p> A fir, 18" dia., bears N.53°W., 32 lks., mkd: ¼ S BT.</p> <p> A fir, 12" dia., bears N.70°E., 8 lks., mkd: ¼ S BT.</p>
<p>GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4717)</p> <p>-----</p> <p>Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:</p> <p>Find the Sec. as reported by the Examiner. I erase the markings on the N face and mark ¼S on W face.</p>
<p>Weyerhaeuser reports rec'd 6/17/1970 - C.S. 55/155A -10 & 11</p> <p>-----</p> <p>12/1968 By Williams FD.</p> <p>OBT 24" Fir N.53°W., 21.1 bark scribed.</p> <p>16" Hemlock S.39°E., 30.0</p>
<p> </p>