

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4678-9)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 9, 10, 15, & 16, mkd T26S S10 on NE, R8W S15 on SE, S16 on SW & S9 on NW faces with 3 notches on E and 4 notches on S edges, from which

- A fir, 30" dia. bears N.32°E., 26 lks mkd: T26S R8W S10 BT
- A maple, 12" dia., bears S.31°E., 18 lks., mkd: T26S R8W S15 BT.
- A maple, 10" dia., bears S.37°W., 36 lks., mkd: T26S R8W S16 BT.
- A fir, 36" dia. bears N.83°W., 51 lks. mkd: T26S R8W S9 BT

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4717)

Correction of surveys as ordered by the Commissioner of the GLO under date of March 18, 1898:

The Cor, to Secs. 9, 10, 15 & 16, as reported in orig. notes on file in the US Surveyor General's Office. From this cor. I trace without re-measuring the surveyed lines & examine each cor, on the W & N bdrs. of the remainder of this tier of Secs. verify the witnesses thereto and where necessary correct markings thereon to correspond with notes, now on file in the U S Surveyor Generals Office.

Weyerhaeuser reports received 6/17/1970 - C.S. File 55/155A

12/1968 By Williams BTs, mks, tag

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #350, surveyed 5/1977 - (DCSO record Vol. 40 Page 15953)

The cor. of secs. 9, 10, 15, & 16, perpetuated & recorded by Robert C. Adamek, Reg. Land Surveyor No. 999, in 1974, for Weyerhaeuser Timber Company, (DCSO does not have this survey) monumented with an iron bolt, $\frac{3}{4}$ " dia., firmly set, projecting 6", above ground, from which the remains of the orig. BTs:

- A sawed fir stump, 34" dia., bears N.32°E., 26 lks., no marks visible.
- A sawed fir stump, 50" dia., bears N.83°W., 51 lks., with scribe marks T26S R visible on bark blaze.

and the remains of bearing trees mid, by Adamek
continued next page

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed cedar stump, 33" dia., bears S.53°E., 10 lks.,
with a nail with "W" embossed on head, at base.
A sawed cedar stump, 28" dia., bears S.47¼°W., 55 lks.,
with a nail with "W" embossed on head, at base.
At the corner point
Set an iron post, 28" long, 2½" dia. 24" in the ground,
directly over iron bolt, with brass cap mkd:
T26S R8W
S 9 | S 10
S 16 | S 15
1977
No suitable trees available within limits.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 3/31/2026 - C.S. File 67/62-35

Found - BLM brass cap, projecting 16" (properly mkd)
25"x4' sawn cedar stump S.43½°w., 35.2 ft. (rec.
S.47¼°W., 55 lks)
New - 24"x 1' sawn D.Fir stump, N.16°E., 6.5 ft.
16"x 3' sawn D.Fir stump, S.74°E., 10.4 ft.
15"x 1' sawn D.Fir stump S.15°W., 17.8 ft.
3 new stump B0s are spiked with 3½" mag nail, top
center.
Note - Compass decl. 14¼°E.
Corner is 60 ft. north of logging road on north
facing bench.
Trimble GEO XT position:
N 43.31599394° W 123.64488733°