

TOWNSHIP 26 RANGE 08 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 11 Page(s) 4680)

Set live oak post, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd 1/4 S on W face, from which
A live oak, 5" dia., bears N.66°E., 11 lks., mkd: 1/4 S BT.
A fir, 18" dia., bears N.36°W., 4 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #350, surveyed May 1977 - (DCSO records Vol. 40 Page(s) 15954)

The 1/4 sec. cor. of secs. 9 & 10, determined at record bearing & distance from the remains of the orig. BTs:
An oak snag, 6" dia., bears N.66°E., 11 lks., no marks visible on decayed blaze.
A fir, 30" dia., bears N.36°W., 4 lks., with scribe marks 1/4 S BT visible on bark blaze, & a nail with "W" embossed on head, at base.
and a bearing tree of which I have no record
A fir, 25" dia., bears N.72 1/2°E., 35 1/2 lks., with a nail with "W" embossed on head, at base.

At the corner point
Set an iron post. 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd.
T26S R8W
1/4
S 9 | S 10
1977