

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C. Flint, Under Contract #392,
dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3931)

Cor. of secs. 3, 4, 33 and 34, Set Fir post 4 ft. long, and
4" sq., from which

- A Cedar 15" dia., bears S.85°E., 4 lks. dist.
- A Cedar 20" dia., bears S.40°E., 5 lks. dist.
- A Cedar 12" dia., bears N.88°W., 8 lks. dist.
- A Maple 14" dia., bears N.14°E., 8 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 1968 - C.S. File 54/72-32

Found - Orig. 15" now 30" Cedar, alive but leaning badly,
S.85°E., 2.6 ft., faint scar.

Orig. 20" now 36" Cedar, 8 ft. high snag, S.40°W.,
(Rec. S.40°E.) 3.3 ft., open and find reverse
scribe.

Orig. 12" now 22" Cedar, alive, N.88°W., 5.3 ft.,
shows faint scar. Rescribed "T25S R8W S33 CS BT"
No trace of NE. Maple orig. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T25S	R8W	S 33	S 34
T26S		S 4	S 3

1968

New BTs- 60" D.Fir S.25°E., 30.8 ft. mkd. T26S R8W S3 CSBT
26" Hemlock S.16°W., 32.2 ft. mkd. T26S R8W S4 CS BT
8" Hemlock N.41°E., 21.2 ft. mkd. T25S R8W S34 CS BT
Corner lies on very steep W. slope about 150 ft. E. of bench.

Weyerhaeuser reports received 6/17/1970 - C.S. 55/155A-2 -
added 3/14/2019)

FD. 6/1963 - Stevens & Party

- 56" D.F. 'W' nail, tag N.47°E., 65.8 ft.
- 28" Cedar 'W' nail, tag S.85°E., 2.6 ft
- 26" W.Fir 'W' nail, tag S.16°W., 31.1 ft
- 20" Cedar 'W' nail, tag N.88°W., 4.4 ft.